

Teledex Diamond Series

- Single and Two-Line Telephone
- Integrated Speakerphone – Hands-free conversations*
- Guest Service Buttons – Up to ten (10) for one-touch access to hotel services
- ADA Handset Volume Boost – Three (3) distinct levels, compliant with HAC/VC and FCC requirements
- Raised Red Message-Waiting Lens – Easily seen from any area in the guestroom
- Message-Waiting Circuitry – Message Waiting will activate on high or low voltage; Guarantees operation of up to 7 phones for suite applications, with an extra-bright message-waiting lamp
- Mute Key – Deactivates microphone during speakerphone and handset calls; a red LED indicates activation**
- Speaker On/Off Key – With red LED for easy speakerphone activation*
- Electronic 3-way Call Conference Function with LED indicator for convenient multi-line conversations***
- Hold Key – Places the active line on hold so the second line can be used or a conference call initiated***
- Hold Release Detection Circuit – Releases calls on hold when line is accessed by any telephone

- Redial Key – Automatically redials the last number dialed, with timed deletion of the last number after 30 minutes for enhanced hospitality security (most models)
- Flash Key (most models)
- Textured Finish – Provides durable resistance against scratches and smudges
- Full-Length Paper Faceplate – Allows user-friendly customization
- Desk or Wall Mountable – Provides placement flexibility
- Hidden Programming Key – Eliminates arbitrary reprogramming of autodial keys

*Speakerphone models only

**Not available in single-line basic or lobby phone

***Two-line only



TELEDEX DIAMOND SERIES

SPECIFICATIONS

Standard Color: Ash and Black
Footprint (Desk):
 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 2.5" (6.35cm) (d) (without handset);
 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 3.75" (9.53cm) (d) (with handset)
Footprint (Wall):
 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 2.13" (5.41cm) (d) (without handset);
 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 3.25" (8.23cm) (d) (with handset)
Weight: 1.85 lbs. (0.83kg)
Packaging: 10 per carton
Faceplate Size: 3.13" (w) x 8.75" (l)
FCC Specifications: Meet or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard: ETL and CE

Operating Voltage: 24 to 56 VDC Non-Polarity
Signaling: Standard 12 tone
 DTMF no Pulse/Rotary dialing
Flash Timing: 100 mS to 1000mS
Ringer Equivalence: Z
Cabling: 2 pair minimum
Registered Connector: USOC RJ-14
Handset: Hearing Aid compatible
 Standard "K" type
Handset Cord: 10-foot coil cord
Line Cord: 12-foot, 2 pair

PART NUMBERS

Diamond Lobby

DIA 65009 Ash
 DIA 650091 Black

Diamond Basic

DIA 65309 Ash
 DIA 653091 Black

Diamond +

DIA 65039 Ash
 DIA 650391 Black

Diamond +3

DIA 65739 Ash
 DIA 657391 Black

Diamond +5

DIA 65139 Ash
 DIA 651391 Black

Diamond +10

DIA 65239 Ash
 DIA 652391 Black

Diamond +s-3

DIA 65749 Ash
 DIA 657491 Black

Diamond +s-5

DIA 65149 Ash
 DIA 651491 Black

Diamond +s-10

DIA 65339 Ash
 DIA 653391 Black

Diamond +s

DIA 65039 Ash
 DIA 650391 Black

Diamond L2-E

DIA 67059 Ash
 DIA 670591 Black

Diamond L2-5E

DIA 67159 Ash
 DIA 671591 Black

Diamond L2-10E

DIA 67259 Ash
 DIA 672591 Black

Diamond L2s-5E

DIA 67149 Ash
 DIA 671491 Black

Diamond L2s-10E

DIA 67359 Ash
 DIA 673591 Black

U.S. Toll Free 1 800 794 8353
 Telephone +1 719 638 8821
 Fax +1 719 638 8815

info@teledex.com
 teledex.com