

TELEDEX[®]

SMALL IS THE NEW BIG.



E SERIES

Amazingly big on features, yet surprisingly small in size.

E SERIES

Available in single and two-line, analog, VoIP, corded, and cordless configurations, micro-footprint Teledex E Series phones have created an entirely new hotel guestroom telephone category. Originally designed to meet the limited space requirements aboard cruise ships, E Series phones require less room on the hotel guestroom desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller as well.

Small is the new big.



E Series VoIP Corded

- Optional LCD display with Indication for Speaker & Mute Keys, LED Indication for Hold, Line 1 & Line 2 Keys (2 line models only), and LCD digital clock screen
- Single or Two line speakerphones
- Up to Seven (7) Configurable Soft Keys (line & features)
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- Available in Ash or Black
- ETrim available

*Two-line only

E Series VoIP Cordless

- Available Frequencies: 1.8 GHz or 1.9 GHz
- Single or Two line speakerphones
- Supports up to five handsets, including one on the base and four remotes
- Up to Seven (7) Configurable Soft Keys (line & features)
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- RediDock available
- Available in Ash or Black

*Two-line only

E Series Analog Corded

- Single or Two line speakerphones
- Eight (8) Configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- Electronic 3-way conference*
- Available in Ash or Black
- ETrim available

*Two-line only

E Series Analog Cordless

- Available Frequencies: 1.8 GHz or 1.9 GHz
- Single or Two line speakerphones
- Supports up to five handsets, including one on the base and four remotes
- Eight (8) Configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference*
- RediDock available
- Available in Ash or Black

*Two-line only

E SERIES VoIP

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint (Desk):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand)
Footprint (Wall):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount)
Footprint (ETrim/RediDock):	Same as above
Weight:	2.0 lbs. (0.9kg)
Weight (ETrim/Redidock):	12 oz. (0.34kg)
Frequency:	1.9 GHz or 1.8 GHz
Power:	Power over Ethernet (POE) 802.3af Compliant
Power (Cordless):	Remote Charging Station includes Handset with Battery & A/C adaptor
Standby Time (Cordless):	10 days

PART NUMBERS

SINGLE-LINE SIP CORDED

E100IP

EV021000S07D	Ash
EV011000S07D	Black

E100IPTRM

EV021000S00T	Ash
EV011000S00T	Black

E100IPLBY - Lobby

EV021000N00L	Ash
EV011000N00L	Black

TWO-LINE SIP CORDED

E200IP

EV022000S07D	Ash
EV012000S07D	Black

E200IPTRM

EV022000S00T	Ash
EV012000S00T	Black

Talk Time (Cordless):	6 hours
Range (Cordless):	100ft (30m)
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	10 per carton
Packaging (RediDock):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	FCC Part 15 Subpart B: 2009
Safety Standard:	UL - 60950-1 2nd edition
Handset:	10 ft (3.048m)
Line Cord:	RJ14 line cord - 15 ft (4.5m)
Line Cord (Cordless):	RJ45 line cord - 15 ft (4.5m)

RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

SINGLE-LINE SIP CORDLESS

E103IP - 4 Speed Dials

EV021319S04D	Ash
EV011319S04D	Black

E103IP - 7 Speed Dials

EV021319S07D	Ash
EV011319S07D	Black

E103IP-RediDock

EV021319S00H	Ash
EV011319S00H	Black

TWO-LINE SIP CORDLESS

E203IP - 4 Speed Dials

EV022319S04D	Ash
EV012319S04D	Black

E203IP - 7 Speed Dials

EV022319S07D	Ash
EV012319S07D	Black

E203IP-RediDock

EV022319S00H	Ash
EV012319S00H	Black

E SERIES ANALOG

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint (Desk):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand)
Footprint (Wall):	4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount)
Footprint (RediDock):	Same as above
Weight:	1.4 lbs. (0.64kg)
Weight (Redidock):	10 oz. (0.29kg)
Frequency:	1.9 GHz or 1.8 GHz
Power:	Adapter
Power (Cordless):	Remote Charging Station includes Handset with Battery & A/C adaptor
Standby Time (Cordless):	10 days
Talk Time (Cordless):	6 hours
Range (Cordless):	100ft (30m)

Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	10 per carton
Packaging (RediDock):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	Meets or exceeds Part 68, FCC Part 15 & UL 1459 Ref.
Safety Standard:	UL - 60950-1 2nd edition
Operating Voltage:	24 to 56 VDC Non-Polarity
Flash Timing:	600 ms
Ringer Equivalence:	Z (Use only behind PBX)
Handset:	10 ft (3.048m)
Line Cord:	RJ14 line cord - 15 ft (4.5m)
Line Cord (Cordless):	RJ45 line cord - 15 ft (4.5m)

PART NUMBERS

SINGLE-LINE ANALOG CORDED

E100 - 4 Speed Dials

EA021000S04D	Ash
EA011000S04D	Black

E100 - 8 Speed Dials

EA021000S08D	Ash
EA011000S08D	Black

E100TRM

EA021000S00T	Ash
EA011000S00T	Black

E100LBY - Lobby

EA021000N00L	Ash
EA011000N00L	Black

TWO-LINE ANALOG CORDED

E200 - 4 Speed Dials

EA022000S04D	Ash
EA012000S04D	Black

E200 - 8 Speed Dials

EA022000S08D	Ash
EA012000S08D	Black

E200TRM

EA022000S00T	Ash
EA012000S00T	Black

SINGLE-LINE ANALOG CORDLESS

E103 - 4 Speed Dials

EA021319S04D	Ash
EA011319S04D	Black

E103 - 8 Speed Dials

EA021319S08D	Ash
EA011319S08D	Black

E103-RediDock

EA021319S00H	Ash
EA011319S00H	Black

TWO-LINE ANALOG CORDLESS

E203 - 4 Speed Dials

EA022319S04D	Ash
EA012319S04D	Black

E203 - 8 Speed Dials

EA022319S08D	Ash
EA012319S08D	Black

E203-RediDock

EA022319S00H	Ash
EA012319S00H	Black

