



MORE THAN JUST A TELEPHONE.



M SERIES STANDARD

Sophisticated styling. Smart technology.

M SERIES STANDARD

M Series Standard hotel phones are available in analog, VoIP, corded, and cordless configurations. Choose 0, 5, or 10 guest service keys on the phone, and 0, 3, or 6 on the RediDock remote handset kit. USB charging ports on the phone and RediDock support smart device recharging. Optional alarm clock with remote control. OneTouch voice mail retrieval automates guest messaging. AutoSync registers RediDock handsets with the base to eliminate connection failures and misplaced handsets.

National Account Package

Place your minimum 50-phone Teledex M Series Standard order and receive:

- Free printing and installation of full-color faceplates with room numbers.
- Free 10% spare faceplates.
- Free speed dial key pre-programming.
- Free ground shipping within the Continental U.S.

Matching MTRM Trimline available.



Versatile M Series Standard front/rear facing RediDock remote handset kits.



M Series Standard Analog Cordless

- Available Frequencies: 1.8 GHz and 1.9 GHz
- Single or Two-line speakerphones
- Handset speakerphone
- Supports up to five handsets, including one on the base and four remotes (RediDocks)
- 0, 5, or 10 configurable guest service keys on base
- 0, 3, or 6 configurable guest service keys on handset
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- 2 side USB power ports for device charging
- Electronic 3-way conference (2-line only)
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Available in Black

M Series Standard VoIP Cordless

- Available Frequencies: 1.8 GHz and 1.9 GHz
- Single or Two-line speakerphones
- Handset speakerphone
- Supports up to five handsets, including one on the base and four remotes (RediDocks)
- 0, 5, or 10 configurable guest service keys on base
- 0, 3, or 6 configurable guest service keys on handset
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- 1 side USB power port for device charging
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference (2-line only)
- Full-length customizable paper faceplate
- Available in Black

M Series Standard Analog Corded

- Single or Two-line speakerphones
- Optional alarm clock with remote control
- 5 or 10 configurable guest service keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- 2 side USB power ports for device charging
- Electronic 3-way conference (2-line only)
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Trimline available
- Available in Black

M Series Standard VoIP Corded

- Single or Two-line speakerphones
- 5 or 10 configurable guest service keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- 1 side USB power port for device charging
- Electronic 3-way conference (2-line only)
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Trimline available
- Available in Black

M SERIES STANDARD VoIP

SPECIFICATIONS

Standard Color:	Black
Footprint:	217 mm x 147.2 mm x 93 mm
Footprint (Trimline):	240 mm x 76.2 mm x 64 mm
Footprint (RediDock):	215 mm x 66 mm x 69 mm
Weight:	2.43 lbs / 1100 g
Weight (Trimline):	1.32 lbs / 600 g
Weight (RediDock):	1.43 lbs / 650 g
Frequency:	1.9 GHz or 1.8 GHz
Power:	Power over Ethernet (POE) 802.3af Compliant
Power (Cordless):	Remote Charging Station includes Handset with Battery & A/C adaptor
Standby Time (Cordless):	10 days
Talk Time (Cordless):	6 hours

PART NUMBERS

SINGLE-LINE VoIP CORDED

M100IP5 - 5 GSK

MV10S5D Black

M100IP10 - 10 GSK

MV10S10D Black

M100IPTRM - Trimline

MV10NT Black

TWO-LINE VoIP CORDED

M200IP5 - 5 GSK

MV20S5D Black

M200IP10 - 10 GSK

MV20S10D Black

M200IPTRM - Trimline

MV20NT Black

SINGLE-LINE VoIP CORDLESS

M103IP5 - 5 GSK/0 GSK HDKIT

MV1319S5D Black

M103IP53 - 5 GSK/3 GSK HDKIT

MV1319S53D Black

M103IP56 - 5 GSK/6 GSK HDKIT

MV1319S56D Black

M103IP10 - 10 GSK/0 GSK HDKIT

MV1319S10D Black

M103IP103 - 10 GSK/3 GSK HDKIT

MV1319S103D Black

M103IP106 - 10 GSK/6 GSK HDKIT

MV1319S106D Black

M103IPHDKT - 0 GSK HDKIT

MV1319SHK Black

Range (Cordless): 100ft (30m)

Humidity: 65% ± 20%

Temperature: 77°F ± 50° (25°C ± 10°C)

Packaging: 10 per carton

Packaging (RediDock): 20 per carton

Faceplate Size: Full length

FCC Specifications: FCC Part 15 Subpart B: 2009

Safety Standard: UL - 60950-1 2nd edition

..... ADA/HAC

Handset Coil Cord: 10 ft (3.048m)

Line Cord: RJ14 line cord - 12 ft (3.66m)

Line Cord (Cordless): RJ45 line cord - 12 ft (3.66m)

RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

M103IP3HDKT - 3 GSK HDKIT

MV1319S3HK Black

M103IP6HDKT - 6 GSK HDKIT

MV1319S6HK Black

M203IP10 - 10 GSK/0 GSK HDKIT

MV2319S10D Black

M203IP103 - 10 GSK/3 GSK HDKIT

MV2319S103D Black

M203IP106 - 10 GSK/6 GSK HDKIT

MV2319S106D Black

M203IPHDKT - 0 GSK HDKIT

MV2319SHK Black

M2033IPHDKT - 3 GSK HDKIT

MV2319S3HK Black

M2036IPHDKT - 6 GSK HDKIT

MV2319S6HK Black

TWO-LINE VoIP CORDLESS

M203IP5 - 5 GSK/0 GSK HDKIT

MV2319S5D Black

M203IP53 - 5 GSK/3 GSK HDKIT

MV2319S53D Black

M203IP56 - 5 GSK/6 GSK HDKIT

MV2319S56D Black

M SERIES STANDARD ANALOG

SPECIFICATIONS

Standard Color:	Black
Footprint:	217 mm x 147.2 mm x 93 mm
Footprint (Trimline):	240 mm x 76.2 mm x 64 mm
Footprint (RediDock):	215 mm x 66 mm x 69 mm
Weight:	2.54 lbs / 1150 g
Weight (Trimline):	1.27 lbs / 575 g
Weight (Redidock):	1.43 lbs / 650 g
Frequency:	1.9 GHz or 1.8 GHz
Power:	Adapter
Power (Cordless):	Remote Charging Station includes Handset with Battery & A/C adaptor
Standby Time (Cordless):	10 days
Talk Time (Cordless):	6 hours
Range (Cordless):	100ft (30m)
Humidity:	65% ± 20%

PART NUMBERS

SINGLE-LINE ANALOG CORDED

M1005 - 5 GSK

MA10S5D Black

M100C5 - 5 GSK, Alarm Clock

MA10S5DC Black

M10010 - 10 GSK

MA10S10D Black

M100C10 - 10 GSK, Alarm Clock

MA10S10DC Black

M100TRM - Trimline

MA10NT Black

TWO-LINE ANALOG CORDED

M2005 - 5 GSK

MA20S5D Black

M200C5 - 5 GSK, Alarm Clock

MA20S5DC Black

M20010 - 10 GSK

MA20S10D Black

M20010 - 10 GSK, Alarm Clock

MA20S10DC Black

M200TRM - Trimline

MA20NT Black

SINGLE-LINE ANALOG CORDLESS

M1035 - 5 GSK/0 GSK HDKIT

MA1319S5D Black

M10353 - 5 GSK/3 GSK HDKIT

MA1319S53D Black

M10356 - 5 GSK/6 GSK HDKIT

MA1319S56D Black

Temperature: 77°F ± 50° (25°C ± 10°C)

Packaging: 10 per carton

Packaging (RediDock): 20 per carton

Faceplate Size: Full length

FCC Specifications: Meets or exceeds Part 68,

..... FCC Part 15 & UL 1459 Ref.

Safety Standard: UL - 60950-1 2nd edition

..... ADA/HAC

Operating Voltage: 24 to 56 VDC Non-Polarity

Flash Timing: 600 ms

Ringer Equivalence: Z (Use only behind PBX)

Handset Coil Cord: 10 ft (3.048m)

Line Cord: RJ14 line cord - 12 ft (3.66m)

Line Cord (Cordless): RJ45 line cord - 12 ft (3.66m)

M10310 - 10 GSK/0 GSK HDKIT

MA1319S10D Black

M103103 - 10 GSK/3 GSK HDKIT

MA1319S103D Black

M103106 - 10 GSK/6 GSK HDKIT

MA1319S106D Black

M103HDKT - 0 GSK HDKIT

MA1319SHK Black

M1033HDKT - 3 GSK HDKIT

MA1319S3HK Black

M1036HDKT - 6 GSK HDKIT

MA1319S6HK Black

M20353 - 5 GSK/3 GSK HDKIT

MA2319S53D Black

M20356 - 5 GSK/6 GSK HDKIT

MA2319S56D Black

M20310 - 10 GSK/0 GSK HDKIT

MA2319S10D Black

M203103 - 10 GSK/3 GSK HDKIT

MA2319S103D Black

M203106 - 10 GSK/6 GSK HDKIT

MA2319S106D Black

M203HDKT - 0 GSK HDKIT

MA2319SHK Black

M2033HDKT - 3 GSK HDKIT

MA2319S3HK Black

M2036HDKT - 6 GSK HDKIT

MA2319S6HK Black



U.S. Toll Free 1 800 794 8353
Telephone +1 217 239 6533
Fax +1 719 638 8757

info@teledex.com
teledex.com